

Center Latch Elevators Forum's Hydraulic Center Latch Elevators come equipped with a bushing system to handle tubulars with square and tapered load shoulders between 2 3/8" - 9 7/8". Features Pipes ...

Casing heads and casing spools Extensive range TechnipFMC offers an wide range of C-22 and C-29 casing heads and spools covering multiple flange sizes from 7 1/16 to 30-inches. The maximum rated ...

The charts above provide the technical foundation for making informed casing procurement decisions, but successful well construction also depends on understanding how casing grade, connection type, ...

A 20" casing was set at depth of 1200" and a 13 3/8" casing at 4500". The hole diameter is 26" and after the last casing it is 12.25". The pumps discharge rate is 700 gpm and the nozzle velocity is 370 ft/s. ...

The patented external clamping system evenly distributes and maintains gripping force during rotation, reciprocation, and push-down operations to enable running longer, heavier strings at high-circulating ...

The casing head in a conventional wellhead system is the lowest part of the wellhead assembly and is almost always connected to the surface casing string. It supports the remaining parts of the wellhead ...

This document contains 15 supplementary problems related to rotary drilling for oil and natural gas. The problems cover topics such as determining drilling costs, ...

In this article, we shall discuss the major casing applications, types, sizes, grades & specifications in detail. Casing pipes come in various sizes and wall thicknesses, allowing for ...

Our aim is to increase crew safety and improve rig operations with hands-free and fully automated casing handling operations. We are bringing innovations to the drill floor with providing integrating ...

The Weatherford 16-25 hydraulic casing tong provides 25,000 ft-lb (33,900 Nom) of torque capacity for running and pulling 6 5/8- to 16-in. casing. At the heart of this versatile and lightweight tong is a ...

Web: <https://fasteneraibate.nl>